



absolutely™

WD Se™ Datacenter Capacity HDD

Optimal Storage for NAS and Scale-Out Architectures

WD's Se hard drives provide an ideal solution for scale-out datacenters, delivering a cost-effective combination of performance, reliability, and workload capability while maintaining the hardiness of a true enterprise-class design. All WD datacenter storage devices are designed from the ground up to deliver optimal performance and maximum data integrity while running 24x7x365 in demanding multi-slot environments.



INTERFACE	FORM FACTOR	ROTATIONAL SPEED	CAPACITIES
SATA 6 Gb/s	3.5-inch	7200 RPM	1 TB to 4 TB

MODEL NUMBERS

- WD4000F9YZ
- WD3000F9YZ
- WD2000F9YZ
- WD1002F9YZ

Product Benefits

Cost effective enterprise-class storage

Get the right blend of performance, reliability and capacity and keep your total cost of ownership low.

24x7x365 reliability

Choose the storage foundation specifically designed for SMB to high-end NAS and large-scale datacenter replication environments running 24x7x365.

Maximum capacity for hyperscale environments

Build a massive data footprint with capacities up to 4 TB - 144 TB per square foot.

Dual processor

Twice the processing power to maximize performance.

Dynamic fly height technology

Each read-write head's fly height is adjusted in real time for optimum reliability.

Vibration Protection

Enhanced RAFF™ technology includes sophisticated electronics to monitor the drive and correct both linear and rotational vibration in real time. The result is a significant performance improvement in high vibration environments over the previous generation of drives.

Dual actuator technology

A head positioning system with two actuators that improves positional accuracy over the data track(s). The primary actuator provides coarse displacement using conventional electromagnetic actuator principles. The secondary actuator uses piezoelectric motion to fine tune the head positioning to a higher degree of accuracy.

Environmentally responsible

In addition to being RoHS compliant, these drives are built with halogen reduced components.

StableTrac™

The motor shaft is secured at both ends to reduce system-induced vibration and stabilize platters for accurate tracking during read and write operations. (2 TB and above)

Multi-axis shock sensor

Automatically detects the subtlest shock events and compensates to protect the data.

RAID-specific, time-limited error recovery (TLER)

Prevents drive fallout caused by the extended hard drive error-recovery processes common to desktop drives.

NoTouch™ ramp load technology

The recording head never touches the disk media ensuring significantly less wear to the recording head and media as well as better drive protection in transit.

Thermal extended burn-in test

Each drive is put through extended burn-in testing with thermal cycling to ensure reliable operation.

Advanced Format (AF)

Technology adopted by WD and other drive manufacturers as one of multiple ways to continue growing hard drive capacities. AF is a more efficient media format that enables increased areal densities.

Applications

Ideal for bulk cloud storage, replicated environments, content delivery networks (CDNs), SMB to high-end network attached storage (NAS), backup and archiving.

The WD Advantage

WD puts our datacenter products through extensive Functional Integrity Testing (F.I.T) prior to any product launch. This testing ensures our products consistently meet the high quality and reliability standards of the WD brand. Following a FIT test the Enterprise System Group (ESG) testing validates interoperability with HBAs, operating systems and drivers to ensure an even greater level of quality, reliability and peace of mind.

WD also has a detailed Knowledge Base with helpful articles and software utilities. Our customer support lines have longer operational hours to ensure you get the help you need when you need it. Our toll-free customer support lines are here to help or you can access our WD Support site for additional details.

Specifications	4 TB	3 TB	2 TB	1 TB
Model number ¹	WD4000F9YZ	WD3000F9YZ	WD2000F9YZ	WD1002F9YZ
Interface	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s
Formatted capacity ²	4 TB	3 TB	2 TB	1 TB
User sectors per drive	7,814,037,168	5,860,533,168	3,907,029,168	1,953,525,168
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Advanced Format	Yes	Yes	Yes	Yes
Native command queuing	Yes	Yes	Yes	Yes
RoHS compliant ³	Yes	Yes	Yes	Yes
Performance				
Data transfer rate (max)				
Buffer to host	6 Gb/s	6 Gb/s	6 Gb/s	6 Gb/s
Host to/from drive (sustained)	171 MB/s	168 MB/s	164 MB/s	187 MB/s
Cache (MB)	64	64	64	128
Rotational speed (RPM)	7200	7200	7200	7200
Reliability/Data Integrity				
Load/unload cycles ⁴	300,000	300,000	300,000	300,000
Non-recoverable read errors per bits read	<10 in 10 ¹⁵	<10 in 10 ¹⁵	<10 in 10 ¹⁵	<10 in 10 ¹⁵
MTBF (hours) ⁵	1,000,000	1,000,000	1,000,000	800,000
MTBF (hours) for 1-5 bay NAS ⁶	1,200,000	1,200,000	1,200,000	1,000,000
Limited warranty (years) ⁷	5	5	5	5
Power Management				
Average power requirements (W)				
Sequential read	9.5	9.5	7.2	6.2
Sequential write	9.5	9.5	7.2	6.2
Random read/write	9.5	9.5	7.3	7.1
Idle	8.1	8.1	5.9	4.6
Environmental Specifications⁸				
Temperature (°C)				
Operating	5 to 55	5 to 55	5 to 55	5 to 55
Non-operating	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Shock (Gs)				
Operating (2 ms, read/write)	30	30	30	30
Operating (2 ms, read)	65	65	65	65
Non-operating (2 ms)	300	300	300	300
Acoustics (dBA) ⁹				
Idle	31	31	31	30
Seek (average)	34	34	34	34
Physical Dimensions				
Height (in./mm, max)	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.66/0.75	1.66/0.75	1.55/0.70	0.99/0.45

¹ Not all products may be available in all regions of the world.

² As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 6 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

³ WD hard drive products manufactured and sold worldwide after June 8, 2011, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

⁴ Controlled unload at ambient condition.

⁵ Product MTBF and AFR specifications are based upon a 40°C base casting and system workloads of up to 180 TB/year (workload is defined as the amount of user data transferred to or from the hard drive).

⁶ Based on a typical 1-5 bay tabletop NAS product environment under normal operating conditions.

⁷ The term of the limited warranty may vary by region. Visit <http://support.wd.com/warranty> for details.

⁸ No non-recoverable errors during operating tests or after non-operating tests.

⁹ Sound power level.

Western Digital
3355 Michelson Drive, Suite 100
Irvine, California 92612
U.S.A.

For service and literature:
<http://support.wd.com>
www.wd.com
800.ASK.4WDC North America
(800.275.4932)
800.832.4778 Spanish
+800.6008.6008 Asia Pacific
00800.27549338 Europe
(toll free where available)
+31.880062100 Europe/Middle East/Africa



Canada ICES-003 Class B / NMB-003 Classe B

Western Digital, WD, and the WD logo are registered trademarks of Western Digital Technologies, Inc. in the U.S. and other countries; and WD Se, RAFF, NoTouch, StableTrac, and FIT Lab are trademarks of Western Digital Technologies, Inc. in the U.S. and other countries. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.